

<u>atriadesigns.ca</u> 604-428-1818 <u>sales@atriadesigns.ca</u>

## PIAZZINO The natural wooden parasol





## PIAZZINO

> 98 %



| Frame                  | 8 parts   |
|------------------------|---|
|                        | Pole Ø 48 mm  |
|                        | Pulley system for opening and closing, fixed with a metal pin |
|                        | Fabric corners reinforced with (white) leather                |
|                        | Frame roof: round, square                                     |
| Frame colour           | Fabric quality 5, 4: colourless-varnished eucalyptus wood     |
|                        | Fabric quality 2: red-varnished eucalyptus wood               |
| Canopy                 | Fabric quality 5: polyacrylic, 300 g/m², UV protection > 98 % |
|                        | Fabric quality 4: polyester, 250 g/m², UV protection > 98 %   |
|                        | Fabric quality 2: polyester, 220 g/m², UV protection > 98 %   |
| Flounce                | Only available without  |
| Protective cover       | Included in delivery  |
| Electrical accessories | Osyrion Spot LED with integrated battery pack                 |









Using Locations

Fixations

## Assortment


| Nominal size<br>without flounce | Number of<br>ribs | Order no.<br>clear finish | Order no.<br>painted red |
|---------------------------------|-------------------|---------------------------|--------------------------|
| cm                              |                   |                           |                          |
| Ø 300                           | 8 parts           | 173 00 300 751            | 172 00 300 751           |
| Ø 350                           | 8 parts           | 173 00 350 751            | 172 00 350 751           |
| 300×300                         | 8 parts           | 173 00 301 751            | 172 00 301 751           |

| Nominal<br>size | Lateral<br>distance | Pole Ø | Area covered | Height<br>closed | Clear<br>headroom | Total height | Foundation | Minimum<br>weight for<br>base | max. wind<br>speed open<br>perm. |
|-----------------|---------------------|--------|--------------|------------------|-------------------|--------------|------------|-------------------------------|----------------------------------|
| cm              | cm                  | cm     | m²           | cm               | cm                | cm           | cm         | kg                            | km/h (wind force)                |
| A               | AS                  | м      | В            | E                | F                 | G            | С          |                               |                                  |
| Ø 300           | 275                 | 4.8    | 6.4          | 95               | 205               | 260          | 60×60      | 40                            | 30 (5)                           |
| Ø 350           | 325                 | 4.8    | 8.7          | 80               | 205               | 270          | 60×60      | 55                            | 30 (5)                           |
| 300×300         | -                   | 4.8    | 9.0          | 50               | 205               | 275          | 60×60      | 55                            | 30 (5)                           |


The listed measures represent extrapolated average values that may be slightly different on the product ( $\pm$  2 %  $\pm$  5 cm).

The height dimensions are based on the ground socket PX (structure 15 cm). In the base variations these might differ slightly. Apart from the steel base minus 7.5 cm. The max. wind speed limits as per our separate list apply only in the presence of a fix ground anchorage.

In the presence of several parasols, the minimum distance between one parasol and another and between parasols and walls shall be 20 cm.



Loose cover max. 10 cm, concrete thickness min. 30 cm (pay attention to frost depth), Guarantee water drainage



8 parts

8 parts

|    | Accessories   | Absolutely necessary | Order no.      |
|----|---|----------------------|----------------|
|    | Protective cover made of coated, tear-resistant polyester fabric  |                      |                |
| 1  | Protective cover with zip and rod   |                      | 350 01 609 978 |
|    | Electrical accessories  |                      |                |
| 2  | OSYRION Spot LED battery-powered light, set of 2,   |                      | 350 01 563 000 |
| 2  | with remote control, including charger  |                      | 00001000000    |
| 3  | OSYRION Spot LED battery-powered light, set of 4,   |                      | 350 01 563 100 |
|    | with remote control, including charger  |                      |                |
|    | Fixations   |                      |                |
|    | Ground sockets  |                      |                |
| 4  | Ground socket PX, galvanised steel  | Connection tube PX   | 350 01 207 001 |
| 4  | Ground socket PX, high-grade steel 1.4301/304   | Connection tube PX   | 350 01 207 011 |
|    | Wall consoles   |                      |                |
| 5  | Wall bracket Z, 180 mm, galvanised steel  | Support tube Z       | 350 01 205 000 |
|    | _   |                      |                |
| 6  | Bases<br>Concrete base Z, 40kg, Ø 60×8.5 cm   | Support tube Z       | 350 01 109 529 |
| 0  | 1 pallet (20 pieces) concrete base Z, 40 kg, Ø 60 × 8.5 cm  | Support tube Z       | 350 01 109 533 |
| 6  | Concrete base Z, 55kg, Ø 60×11cm  | Support tube Z       | 350 01 109 528 |
|    | 1 pallet (20 pieces) concrete base Z, 55 kg, Ø 60 × 11 cm   | Support tube Z       | 350 01 109 534 |
| 7  | Steel base Z 40 kg, 58.5×58.5×2 cm, galvanised steel  | Support tube Z       | 350 01 109 334 |
| -  | Add-on weight 30 kg, 57.5×57.5×1.7 cm, galvanised steel   |                      | 350 01 100 210 |
|    |   |                      |                |
|    | Bases with castors  |                      |                |
| 8  | $^{\rm s}$ Natural granite base Z, 40 kg, 45 × 45 × 8 cm, natural stone, with castors and retractable handle      | Support tube Z       | 350 01 109 465 |
| 8  | <sup>3</sup> Natural granite base Z, 55 kg, 55 × 55 × 9 cm, natural stone,<br>with castors and retractable handle | Support tube Z       | 350 01 109 445 |
| 9  | <sup>a</sup> Base with castors Z, 55 kg, 65×65×11 cm, light concrete  | Support tube Z +     | 350 01 110 000 |
|    | (without decorative plate) NEW  | Decorative plate     |                |
|    | Decorative plate in grey for base with castors Z, 55 kg, plastic NEW  |                      | 350 01 110 110 |
|    | Decorative plate in anthracite for base with castors Z, 55 kg, plastic NEW  |                      | 350 01 110 120 |
|    | Decorative plate in sand for base with castors Z, 55 kg, plastic NEW  |                      | 350 01 110 130 |
| 10 | $^{\scriptscriptstyle 1.3}$ Base with castors Z, 55 kg, 65 $\times$ 65 $\times$ 11 cm, cast concrete decor        | Support tube Z       | 350 01 102 900 |
|    | <sup>1,3</sup> 1 pallet (5 pieces) base with castors Z, 55 kg, Ø 65×65×11 cm, cast concrete decor                 | Support tube Z       | 350 01 102 950 |
|    | Support tubes/Connection tubes  |                      |                |
| 11 | Support tube Z, Ø 48 / 55 mm, galvanised steel  |                      | 350 01 201 210 |
| 11 | Support tube Z, Ø 48 / 55 mm, galvanised steel, powder coated anthracite  |                      | 350 01 201 282 |
| 11 | Support tube Z, Ø 48 / 55 mm, high-grade steel 1.4301 / 304   |                      | 350 01 201 300 |
| 12 | Connection tube PX, Ø 48 / 55 mm, galvanised steel  |                      | 350 01 206 001 |
| 13 | Connection tube PX, Ø 48/55 mm, galvanised steel, powder coated anthracite  |                      | 350 01 206 082 |
| 12 | Connection tube PX, Ø 48/55 mm, high-grade steel 1.4301/304   |                      | 350 01 206 011 |

<sup>1</sup> while stocks last

 $^{\scriptscriptstyle 3}$  only suitable for smooth, joint free surface coverings







Glatz AG Parasols 2023 Season

glatz.com