

<u>atriadesigns.ca</u> 604-428-1818 <u>sales@atriadesigns.ca</u>



GOLIA 150





Giant central pole (pole diam. 150 mm)



Two movements telescopic opening system for closing above the tables



High-tenacity 6005 aluminum alloy frame



Opening system with driving rod, winch and rollaway endless-screw



Stainless Steel Bolts



MODULAR CANOPY - easy to replace



Collars in tig welded aluminum




Rib-arm joints in nylon



Rigid and lowered airvent



With or whitout 40 Cm perimetrical flounce (type A, B, C, D, E)



Avaible bases



Support base



To be fixed



To be buried

Accessories



Led lights



Heaters




Lateral walls



Gutters



Logo application





BOLTS:

TECHNICAL SHEET

STRUCTURE: 6005 High-tenacity aluminum epoxy powder painted.

PARASOL RIBS: Radial high tenacity aluminum profiles ∅ 65x25x2 Mm.

SUPPORT POLE: Central and round made in epoxy powder painted aluminum diam. Ø 150x3 Mm

WINDPROOF ARIVENT: Standard: Rigid and lowered; Optional: rigid and raised.

JOINTS: In aluminum.

COLLARS: In TIG welded aluminum.

OPENING AND CLOSING SYSTEM: Standard: Two movements telescopic system for closing above the tables with endless

screw, actioned with winch and manual driving rod.

Optional: Two movements telescopic automated for closing above the tables which can be operated with a remote control or a fix push-botton panel. Movement through an hydraulic cylinder commanded by an electro - hydraulic control unit which works at low voltage (12 Volts). Complete with emergency electronic battery charger.manual manoeuvre battery. Complete with 12 Volts battery/60 A/h and electronic battery charger.

See Gaggio Color Collection

In stainless steel.


STRUCTURE COLORS: White - manganese grey - RAL on request

AVAIBLE FABRICS: Technology: PVC;

Technology: PVC Black Out;

Technology: Nautical Resined.

PVC STORAGE CASE: Half PVC Premium storage case.



PARAS. SIZE WHEN OPEN (Cm)	RIBS N°	HEIGHTS (Cm)						WEIGHT (Kg)
		Α	A1	В	С	D	Е	WEIGHT (Kg)
700x700	12	435	415	290	250	100	630	160
800x600	10	395	375	295	255	70	575	160
800x700	10	435	415	305	265	75	615	180
900x650	14	440	420	295	255	60	620	190
Diameter 800	12	402	382	265	225	176	578	170